

STS Precision Pressure Transmitter Ordering Code Effective 2019

■ STS part numbers typically follow the format XXX.XXXX.XXXX.XX.X(range). DARK VERTICAL LINES ON PRICE SHEETS SHOW WHERE THE DOTS GO.

- For example, a common ATM (Amplified TransMitter) part number is 231.9910.0105.00.V(100psi)
- Pressure range and engineering units (ex: 100psi) must be specified in free text.



Analog Depth & Level Transmitters ø 0.75"

ATM/N19	9	4	X	X	X	X	X	X	X	X	X	X	X	X	
Pressure type															
Gauge		1													
Absolute		2													
Pressure range															
3 psi to 360 psi				X	X										
Version															
Closed (Datasheet Fig. 1)					5	5									
Electrical connection¹⁾															
PE cable, black								1	3						
price per foot															
PUR cable, black								1	5						
price per foot															
Output signal															
4 to 20 mA										0	5				
0 to 5 V DC										4	6				
0 to 10 V DC										4	7				
Customized output signal										9	9				
Accuracy															
±0.5% FS												0			
±0.25 % FS												1			
±0.1% FS												2			
Temperature range															
25 to 125°F / -5 to 50°C													4		
25 to 175°F / -5 to 80°C (Only available with PE or FEP cable)													5		
Options															
Anderof fill oil for food applications															
Seals: Viton (Standard)															
EPDM seals															
Kalrez															
													G		
													U		
													S		
													T		

NOTES:

1) Please specify type and length of cable