

**PMC Engineering, LLC**

11 Old Sugar Hollow Road, Danbury, CT 06810 U.S.A

Tel: (203) 792-8686 Fax: (203) 743-2051

Website: www.pmc1.com Email: sales@pmc1.com

**PMC LEGACY SERIES Ordering Code**

**Flush-Mount Seal Gauges**


**PMC Configurator**

<b>Part Number</b>	SGB	XXX	V	Hc	S
<b>Model Construction</b>					
<b>Ranges</b>	0 to 100 psi - Standard Other ranges: 0-15, 0-30, 0-60, 0-200 psi 0-100, 0-200, 0-400, 0-700 and 0-1400 kPa 0-1, 0-2, 0-4, 0-6 and 0-7 Bar 0-1, 0-2, 0-4, 0-7, 0-14 and 0-20 kg/cm <sup>2</sup> <i>For ranges over 200 psi and 1400kPa see SAN Seal Gauges</i>		<b>XXX</b>		
<b>O-Rings</b>	Viton - Good to 400°F		<b>V</b>		
<b>Diaphragm</b>	Hastelloy C - Standard Hastelloy C Retainer: Hastelloy C Retainer Ring upgrade		<b>Hc</b>		
<b>Temperature</b>	Standard Temperature Range - Good to 400°F				<b>S</b>
<b>Options</b>	Back connected: Transmitter and connections with rear mount				
<b>Process Connections:</b>					
316L Stainless Steel Flush Mount Weld-on Nipple included <b>LT-07</b>					
316L Stainless Steel Threaded Nipple with 1 ½" NPTM <b>LT-07-S</b>					
<i>*Contact factory for custom Connections and Reducers.</i>					
<b>Example Ordering Format: PMC - SGB -100 psi -V - Hc - S</b>					

**SAN Flush-Mount Seal Gauges**

**PMC Configurator**

<b>Part Number</b>	SGB SAN	XXX	V	Hc	S
<b>Model Construction</b>					
<b>Ranges</b>	0 to 100 psi - Standard Other ranges: 0-15, 0-30, 0-60, 0-200, 0-300 0-100, 0-200, 0-400, 0-700 and 0-1400 and 0-2000 kPa 0-1, 0-2, 0-4, 0-6 and 0-7 Bar 0-1, 0-2, 0-4, 0-7, 0-14 and 0-20 kg/cm <sup>2</sup>		<b>XXX</b>		
<b>O-Rings</b>	Viton - Good to 400°F		<b>V</b>		
<b>Diaphragm</b>	Hastelloy C - Standard Hastelloy C Retainer: Hastelloy C Retainer Ring upgrade		<b>Hc</b>		
<b>Temperature</b>	Standard Temperature Range - Good to 400°F				<b>S</b>
<b>Options</b>	Back connected: Transmitter and connections with rear mount				
<b>Process Connections:</b>					
Stainless Steel SAN Flush Mount Weld-on Nipple included <b>LT-07-SAN</b>					
316L Stainless Steel Threaded Nipple with 1 ½" NPTM <b>LT-07-SAN-S</b>					
<i>*Contact factory for custom Connections and Reducers.</i>					
<b>Example Ordering Format: PMC -SGB SAN - 100 psi - V - Hc - S</b>					



**PMC Engineering, LLC**

11 Old Sugar Hollow Road, Danbury, CT 06810 U.S.A

Tel: (203) 792-8686 Fax: (203) 743-2051

Website: www.pmc1.com Email: sales@pmc1.com

**PMC LEGACY SERIES Ordering Code**

**Flush-Mount Seal Switches**

**PMC Configurator**

<b>Part Number</b>	SGB/SW	XXX	V	Hc	S
<b>Model Construction</b>					
<b>Ranges</b>	0-5 to 250 psi	XXX			
	<i>Specify opening/closing pressure required</i>				
<b>O-Rings</b>	Viton - Good to 400°F	V			
<b>Diaphragm</b>	Hastelloy C - Standard			Hc	
	Hastelloy C Retainer: Hastelloy C Retainer Ring upgrade				
<b>Temperature</b>	Standard Temperature Range - Good to 400°F				S
<b>Process Connections:</b>					
	316L Stainless Steel SAN Flush Mount Weld-on Nipple <b>LT-07</b>				
	316L Stainless Steel Threaded Nipple with 1 ½" NPTM <b>LT-07-S</b>				
	<i>*Contact factory for custom Connections and Reducers.</i>				
<b>Example Ordering Format: PMC -SGB/SW- XXX - V - Hc - S</b>					

**SAN Flush-Mount Seal Switches**

**PMC Configurator**

<b>Part Number</b>	SGB/SW SAN-	XXX	V	Hc	S
<b>Model Construction</b>					
<b>Ranges</b>	0-5 to 250 psi	XXX			
	<i>Specify opening/closing pressure required</i>				
<b>O-Rings</b>	Viton - Good to 400°F	V			
<b>Diaphragm</b>	Hastelloy C - Standard			Hc	
	Hastelloy C Retainer: Hastelloy C Retainer Ring upgrade				
<b>Temperature</b>	Standard Temperature Range - Good to 400°F				S
<b>Process Connections:</b>					
	316L Stainless Steel SAN Flush Mount Weld-on Nipple Included <b>LT-07-SAN</b>				
	316L Stainless Steel Threaded Nipple with 1" NPTM <b>LT-07-SAN-S</b>				
	<i>*Contact factory for custom Connections and Reducers.</i>				
<i>For Complete Process Connections and Flange listings please see Process Connections, Tools and Accessories page</i>					
<b>Example Ordering Format: PMC -SGB/SW SAN- XXX - V - Hc - S</b>					